

# LEDView730SV

## HQUltra Events 4K Scaler-Switcher for LED Videowalls with HQUltraFast Input Switching



LEDView730 is a dedicated LED videowall image scaler based on Calibre's proprietary class-leading HQUltra 4K image processing technology. HQUltra scaling provides best in class picture quality with low latency video processing.

With its custom LED videowall-optimized scaling algorithms, LEDView730 has a special LED mode with per-edge pixel-accurate image sizing for fast pixel-perfect image alignment of all sources on LED videowalls.

Featuring Calibre's proprietary HQUltraFast input channel switching able to switch input channels in under a quarter of a second, LEDView730 has a wide range of input connectivity for today's digitally connected ProAV world, but still is able to support legacy formats too, all with great image quality.

LEDView730 includes front panel controls with easy to read front panel menu system as well as remote control via inbuilt webserver or easy to implement protocol.


For in-camera use a Genlock input is provided compatible with bi or tri-level sync or black & burst.

Flexible Pan-Tilt-Zoom controls allow selection of an area of interest

Rugged 1U rack-mountable case with integral modular universal mains PSU.

- Perfect scaling with Calibre's HQUltra low-latency 4K best-in-class proprietary scaling algorithms
- HQUltraFast proprietary typical 0.25 seconds input channel switching technology
- LED Videowall Optimized Scaling with per-edge pixel-accurate custom sizing
- Front panel jog-wheel and LCD display for fast easy set-up in the field
- 10 Video Inputs: 2xHDMI 4K, 1xHDMI HD, 1xDisplayPort 4K, 2x3G-SDI 1xVGA, 1xCVBS, 1xDVI-U (DVI/HDMI & VGA/RGBS/YpPr), 1xH.264 HD Streaming Video
- 3 Video Outputs: 1xHDMI 4K, 1xDVI/HDMI, 1x3G-SDI
- Picture in Picture ideal for sports scoreboards
- Brightness, Contrast, Saturation controls for all source types
- RGB calibration controls (not 4:2:0 in to 4:2:0 out)
- Flexible Aspect Ratio Conversion
- Genlock (V-Lock) and Source Lock for in-camera & broadcast applications
- Audio de-embed from HDMI, DisplayPort and 3G-SDI inputs to S/PDIF, re-embed to HDMI outputs
- Multiple outputs for local monitoring of live output feed
- Remote control via webserver or simple API
- Supports LED Videowalls from 4096x2160 to 128x96 pixels





# LEDView730SV

## HQUltra Events 4K Scaler-Switcher for LED Videowalls with HQUltraFast Input Switching

### Inputs

- 2x HDMI 4K
- 1x HDMI HD
- 1x DisplayPort 4K
- 2x 3G-SDI
- 1x DVI-U supporting VESA modes, SD, HD, can be configured as fourth HDMI input. DVI-U input also simultaneously supports VGA/RGBS/YPbPr legacy analog formats with suitable cable.
- 1x VGA Analog
- 1x Composite PAL/NTSC/SECAM
- 1x 1080p HD H.264 Streaming Video Input via Gigabit Ethernet Port
- 1x Genlock reference sync input, supports bi/tri-level or black&burst 50/59.94/60Hz formats

HDCP supported on all HDMI/DVI/DisplayPort I/O

### Supported digital input and output formats:

- 4K/UHD (HDMI 4K/DisplayPort / )
- 3840x2160p, 4096x2160p 23.97/24/25/29.94/30/50/59.94/60;
- UHD/4K 50/59.94/60p modes supported in 4:2:0 format.
- HD 1280x720p, 1920x1080i, 1920x1080psf,
- 1920x1080p23.97/24/25/29.94/30/50/59.94/60,
- 2048x1080p23.97/24/25/29.94/30/50/59.94/60.
- ED 480p, 576p (not via SDI), SD 625i (576i), 525i (480i)
- Common VESA graphics formats from VGA to 4K,
- (Modes higher than WUXGA on 4K-capable input channels only)
- Note: Some 4K zoom functionality is limited/unavailable when PIP is in use

### Outputs

- 1x HDMI 4K via HDMI connector
- 1x DVI/HDMI via DVI connector
- 1x 3G-SDI
- 1x S/PDIF digital audio via RCA
- NB: 3G-SDI output is disabled with HDCP-encrypted input and also for incompatible output modes.
- All outputs are otherwise available simultaneously, with the same image shown on each.

### Supported Switching & Sync Modes

- HQUltraFast input Switching in Genlock and Free-Run modes
- Also supports Source Lock when HQUltraFast not required

### User Controls

- Front panel jog-wheel and LCD menu display for fast set-up.
- Keypad for direct input selection and integral indicator LEDs.
- Remote control via RS232, TCP/IP API and Web Server.
- Gigabit Ethernet for webserver and remote control API

### Power Requirements

- 100-264VAC, 50W typical

### Warranty

- 3-years return to base warranty covers parts and labour.

### Order Codes

- LEDView730SV – Order Code L730SV



Model >	H210	H310	H320	H325	L530	H620	H625	H630	H670	H730	H770	L720	L725	L730	L770
Front LCD menu or OSD control	OSD	OSD	OSD	OSD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD	LCD
HDMI 4K Inputs						■(2)	■(2)	■(2)	■(2)	■(2)	■(2)	■(2)	■(2)	■(2)	■(2)
HDMI HD Input															
DVI/HDMI HD Input															
HDBaseT 4K Input															
DisplayPort 4K Input															
Component Input			BNCs	BNCs	BNCs	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U	DVI-U
Composite Input(s)															
VGA Analog Input			DVI-I	DVI-I											
3G-SDI Input(s)								■(2)	■(2)	■(2)	■(2)			■(2)	■(2)
DVI / HDMI HD Output															
HDMI 4K Output															
HDBaseT 4K Output															
VGA Analog Output															
3G-SDI Output															
3G-SDI Audio embed/de-embed & SPDIF															
HQV Processing															
HQUltra 4K Low-Latency Processing															
HQUltraFast High Speed Input Switching															
PIP															
TCP/IP Webserver & API Control															
Geometry Correction, 4-Corner, Rotate															
Mesh-based Warp, config via PC App															
Genlock - V-Lock															
Pan, Zoom, Tilt															
Edge Blending															
Edge Blend Black Level Correction															
Videowall mode with auto PTZ															
LED Videowall Per-Edge Sizing															
Analogue Audio In, Out and Power Amp fitted to models with "A" suffix															
Streaming Video Input via Network Port fitted to models with "SV" suffix															

Calibre UK Ltd,  
Cornwall House, Cornwall Terrace,  
Bradford,  
West Yorkshire  
BD8 7JS, UK

proavsales@calibreuk.com  
EMEA +44 1274 940770  
Americas +1 916 282 1067  
APAC +886 989 997 068  
www.calibreuk.com